

EM-M10004-GPI

VHF 2dB Ground Plane Independent Antenna 132-174 MHz

- High Performance, Broadband Impedance Match •
- Optimized VSWR for Maximum "No Ground Plane" Efficiency ٠
- Black Chrome Finish
- O-ring Seals for Waterproof Construction
- Durable Xenoy[™] Base with TPV Molded Dust Seal and Grip Ring •

| Electrical opeometations | |
|--------------------------|-----------------------------------|
| Frequency Band | 132-174 MHz (Tunable Range) |
| Operational Bandwidth | 15-20 MHz (frequency dependent) |
| VSWR | <1.2:1 at center frequency |
| | <2:1 across operational bandwidth |
| Impedance | 50Ω |
| Gain | 2 dBi |
| Power Rating | 150 W |
| Polarization | Linear, Vertical |
| E-Plane | 70 Degrees, Nominal |
| H-Plane | Omnidirectional |

Electrical Specifications

Mechanical Specifications

| Overall Length (max) | 50 in. (1.27 m) |
|--------------------------------|------------------------------------------------------|
| Whip Material, Finish | 17-7 SS, Black Chrome |
| Base Material | Xenoy™ w/TPV over mold grip ring |
| Spring Material | 17-7 SS, Black Chrome |
| Mounting Application | ³ / ₄ inch thru-hole NMO Mount |
| NMO Cable Assembly & Connector | Sold separately |
| Operating Temperature | -40° to 85° C |
| Corrosion | Salt Fog |
| Humidity | 95% |
| | |

ELECTRO-MAGWAVE, INC.

6111 Carey Drive, Unit #1, Valley View, Ohio 44125 1216-453-1160 f 216-447-8828 www.emwaveinc.com