


NMO 3/4" Hole Mount Assembly

**EM-M11001
NMO to N Type Jack**



- Low profile
- Ease of installation:
Designed for a one-man installation from above
- All brass components with silver plated contact
- Heavy-duty mounting claw for reliable contact and ground connections
- For RG-58/U and 195 cable types



**EM-MTR11001
Thick Panel**

Up to
1/2 in. (12.7mm)
thickness

- Self-adjusting NMO locking nut eliminates guesswork and decreases installation time
- All brass and stainless steel components for maximum reliability and corrosion resistance
- Non-rotational heavy-duty centering washer ensures perfect hole alignment while optimizing non-slip clamping pressure

	Standard Low Profile		Thick Panel Series	
Attached Cable Models	EM-M11001-058	EM-M11001-195	EM-MTR11001-058	EM-MTR11001-195
Frequency Band	30-1000 MHz			
VSWR	1.5:1 typical		<1.3:1 typical	
Powering Rating	100 W @1000 MHz		150 W for VHF 100 W for 700-1000 MHz	
Cable Type	RG-58/U	Low Loss 195	RG-58/U	Low Loss 195
Cable Length	17 ft. (5.1 m) standard length; 35 ft. (10.67 m) available			
Connector	Sold separately			
Mounting Material	Brass		Brass and stainless steel with bright nickel finish	

Specifications subject to change without notice.