## **Product Data Sheet**

# EM-P90918 VHF Broadband Portable Antenna 150-174 MHz

### **Direct OEM Replacement Antenna**

- > Broad Band, 24 MHz Bandwidth with High Directivity Aperture
- ➤ Eliminates Multiple Narrowband Antenna SKU's
- ➤ Direct Replacement, All VHF Bands (150-174 MHz)
- > Flexible, Rugged, Weatherproof Molded Construction
- Soft Durometer TPE Housing Augments Improved Ergonomics
- Color Coded Frequency Identification
- Alternate OEM Connectors Available<sup>†</sup>
- Consult Factory for Detailed Radio Interface Requirements

#### **Electrical Specifications**

Frequency Band	150-174 MHz
VSWR	2.0:1
Impedance	50Ω
Gain	Unity
Power Rating	10 Watts
Polarization	Vertical
Radiation Pattern	Omni Directional

#### **Mechanical Specifications**

Length	11.2 in. (284 mm)
Connector Options <sup>†</sup>	SF (SMA Jack, Motorola <sup>TM</sup> Type) SFK Type (SMA Jack, Kenwood <sup>TM</sup> Type)
(Add suffixes: -SF, -SFK, -SM)	SFK Type (SMA Jack, Kenwood <sup>TM</sup> Type)
,	SM Type (SMA Plug)
Over-Mold Material	Thermoplastic Elastomer (TPE)
Connector Material, Finish	360 Brass, Nickel Plating
Weight	2.05 oz. (58.1g)
Operational Temperature	-20°C to 65°C
Storage Temperature	-40°C to 85°C

Motorola<sup>TM</sup> is a registered trademark of Motorola Trademark Holdings, LLC. Kenwood<sup>TM</sup> is a registered trademark of JVCKenwood Corporation. Specifications subject to change without notification.