



## P15 Series 900 MHz

### 890-942 MHz - 140 Watts Output Power

Frequency Range:	890-942 MHz
Operating Voltage:	+13.8 VDC
Current Draw:	43 Amperes (Max)
Duty Cycle:	100%
Power Input:	See chart below
Power Output:	140 Watts, set at factory
Spurious & Harmonics:	Meets FCC Requirements
Input/Output Impedance:	50 ohms (Nominal)
Load VSWR Tolerance:	VSWR Protected
Indicator LEDs:	DC On, Low Output, High VSWR, High Temp
Alarm:	Summary Alarm Pin ( <b>Open Collector, LOW when Alarm</b> )
Input/Output Connector:	Type 'N' Female
Cooling Method:	Fan Forced Air Over Heat sinks
Operating Temp. Range:	-30 <sup>0</sup> C to +60 <sup>0</sup> C
Storage & Transport:	-40 <sup>0</sup> C to +70 <sup>0</sup> C
Humidity:	80% at +40 <sup>0</sup> C (non-condensing)
Altitude:	10,000 feet maximum

### SIZE

Vertical Mounting:	10.0"
Horizontal Mounting:	19.0"
Depth:	6.0"
Weight:	14 pounds nominal

### POWER INPUT RANGE

<u>Model Description</u>	<u>Required Power In</u>	<u>Power Output</u>
P15-R1L1-C6-001	100-200 mW	140 W
P15-R2L1-C6-001	200-500 mW	140 W
P15-R5L1-C6-001	500 mW-1 W	140 W
P15-1L1-C6-001	1-2 W	140 W
P15-2L1-C6-001	2-5W	140 W
P15-5L1-C6-001	5-10 W	140 W
P15-10L1-C6-001	10-20 W	140 W
P15-20L1-C6-001	20-50 W	140 W

*\* XX-Insert the letter definition for the frequency range chosen  
 By-Pass Circuits, T/R Switch and Power supplies are available.  
 Please call for Details*

Crescend Technologies, LLC · 140 E. State Parkway · Schaumburg, IL 60173  
 Phone: (800) USA-MADE / (847) 908-5400 Fax: (847) 908-5408 · www.crescendrf.com

These specifications are subject to change without notice.